

# INSULFLEX

## INSULATED FLEXIBLE DUCT CONNECTOR

Pat. No. 4183557

### THE ONLY INSULATED FLEXIBLE DUCT CONNECTOR



#### HIGHLIGHTS

• Insulated • 4.2 R Value • Quality Construction • Economically Priced

**Energy Efficient, Superior Construction and Economically Priced.**

**New Advanced INSULFLEX** insulated flexible duct connector completes the "insulated" in insulated duct work. INSULFLEX featuring an "R" value of 4.2 with 25% thicker insulation, is a non-porous product that eliminates air leakage.

When excellence is combined with state-of-the-art HVAC technology, the result is a product of true distinction. **New Advanced INSULFLEX** is the obvious choice for totally efficient insulated duct work.

#### Specifications

FABRIC		FIBERGLASS INSULATION	
<ul style="list-style-type: none"> <li>Flame Resistance - passes California Fire Marshal F102.4 on Flame Retardancy</li> <li>Total Fabric Thickness - .022 Approx.</li> <li>Thread Count - 28 x 14</li> <li>Tensile Strength: Warp - 70 lbs. per inch Fill - 70 lbs. per inch</li> <li>Tear Strength: Warp - 8 lbs. per inch Fill - 11 lbs. per inch</li> <li>Adhesion - 30 lbs./2"</li> <li>Coating - Vinyl</li> <li>Heat Resistance: Continuous - 180° Intermittent - 200°</li> <li>Waterproof</li> <li>Air Tight</li> <li>Resistance to grease, oil, gasoline &amp; acid</li> </ul>		<ul style="list-style-type: none"> <li>Thickness: Nominal 1"</li> <li>Density: .75 lbs.</li> <li>Designed to meet NFPA-90A</li> <li>"R" Value: 4.2</li> </ul>	
		STEEL	
		<ul style="list-style-type: none"> <li>Thickness: 28 Gauge</li> <li>Coating: Galvanized Steel</li> <li>Meets ASTM-A-525-G60</li> </ul>	

#### Ordering Information

ITEM NO.	DESCRIPTION	APPROX. DIM. (IN.)	APPROX. LBS.
10173	IDC-343 INSULFLEX Shipped in 100' Rolls	29 x 29 x 10	65

<b>Duro Dyne East Division, Bay Shore, NY</b>	<b>631-249-9000</b>	<b>Fax: 631-249-8346</b>
<b>Duro Dyne Midwest Division, Fairfield, OH</b>	<b>513-870-6000</b>	<b>Fax: 513-870-6005</b>
<b>Duro Dyne West Division, Santa Fe Springs, CA</b>	<b>562-926-1774</b>	<b>Fax: 562-926-5778</b>
<b>Duro Dyne Canada, Lachine, Quebec, Canada</b>	<b>514-422-9760</b>	<b>Fax: 514-636-0328</b>
<b>www.durodyne.com E-mail: durodyne@durodyne.com</b>		



©2005 Duro Dyne Corporation  
Printed in USA 07/2005  
BC010400